

HARVEST READY





Features and Benefits

- Increased Traction
- Increased Flotation
- Increased Drive Efficiency
- Low Surface Damage
- Maintain Higher Ground Speeds
- Improved Stability
- Easy Installation
- Low Maintenance
- Capacity for Largest Combines



Oscillation Stop

“I couldn’t have gotten the crop out without the tracks. Initially the tracks came with a set of belts for up North and had some traction problems, but ATI came and engineered new tracks with an aggressive tread that worked well. They were behind the customer and served them all the way. They didn’t drop the product off and leave.”

— Wayne Wilkinson, Wilkinson Farms,
Marion, AR

“ATI tracks worked great. We could not have finished getting our rice harvested in such extreme conditions.”

—Terry Schmidt, Green Acre Farms,
Clarksdale, Miss.



ATI Track Models

Standard Module



High Idler Module



Standard Module Specifications

High Idler Module Specifications

| | | | | |
|-------------|--------------|----------------------------|-------------|--------------|
| 37,500 lbs | 17,045 kg | Track Module Load Capacity | 37,500 lbs | 17,045 kg |
| 6,500 lbs | 2,948 kg | Track Module Weight | 7,500 lbs | 3,409 kg |
| 67 in | 1,701 mm | Track Module Height | 67 in | 1,701 mm |
| 86 in | 2,184 mm | Track Module Length | 100 in | 2,540 mm |
| 36 in | 914 mm | Track Module Width | 36 in | 914 mm |
| 36 in | 914 mm | Belt Width | 36 in | 914 mm |
| 3,095 sq in | 19,970 sq cm | Ground Contact Area | 3,095 sq in | 19,970 sq cm |
| 178 in | 4,521 mm | Rolling Circumference | 178 in | 4,521 mm |



ATI, Inc.
103 Brown Street
P.O. Box 686
Mt. Vernon, IN 47620
Website: Ati-tracks.com
Sales: (641) 203-0409
blhannam@gmail.com